

3334 South Tech Blvd Miamisburg, OH 43542 Phone: 800-394-0678 Fax: 937-886-9300

## TECHNICAL DATA SHEET

## EAGLITE NDT FLUID (Non-Destructive Testing Fluid)

NDT Fluid has been formulated to be used as a testing media for non destructive testing of nodular & cast iron castings. It can also be used as an excellent grinding fluid as well as for several months of indoor rust protection of steel parts. It has unsurpassed quality of nonfoaming. Rust protection & clarity with high tolerance for the contamination. NDT Fluid does not contain any nitrite or nitrate thus avoiding the possibility of nitrosoamine formation (which has been found Carcinogenic in animals) while it is under use or staying in a drum. Its' wetting & rust prevention qualities are excellent. Since the NDT Fluid would not turn cloudy/milky at higher temps, one can use re-circulating/condensed warm water from the plant without affecting the clarity of the bath.

## SPECIFICATIONS:

Color: Available in Green or Amber Yellow

Odor: Bland

Wt/Gal: 8.8#

Foam Test: 0.0" height of foam in blender test. Circulating pump also gave the same

results.

pH: 7.4 - 8.4 (2% solution in water)

Corrosion Test: (Cast iron chips) No rust for more than 8 weeks (3% solution in water)

Oil Emulsion: Does not emulsify tramp oil.

Bath Make-Up: 3-7% by volume in water (10-15% recommended in highly corrosive

environment)

Warranty Disclaimer: Since the actual use of our products and the above information by others is beyond our

> control, we make no guarantee, expressed or implied as the effects of such use or the results obtained even though the technical information and suggestions for use contained herein are believed to be accurate and reliable. The above product and the process are

not intended to violate any patent rights.